

Integra®

Classic style with adjustable temples

HBA
SYSTEM INTEGRATORS
High-tech solutions for defense industries



PYRAMEX
THE PEAK OF SAFETY AND STYLE



Black Frame

Part

SB410S •••

SB410ST •

SB420S •••

SB430S •••

SB450SF ••

SB460SF ••

Lens

Clear

Clear Anti-Fog

Gray

Amber

5.0 IR Filter

3.0 IR Filter

Black Ratchet Frame

SB410SR •

Clear

Mixed Blue Frame

SM410S • Clear

Blue Frame

SN410S •• Clear

Red Frame

SR410S • Clear

Red, White, and Blue Frame

SNWR410S • Clear

- Single lens and adjustable temples ensure reliable performance.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

GENERAL SPECIFICATION

Bridge: N/A

Lens Base: 4.0 Curve

Lens Size Diagonal: 138mm

Lens Size Vertical: 39mm

Lens Thickness: 2.0mm

Overall Length (Lens-Tip): 85mm













Overall Width (Hinge-Hinge): 149mm

PD: 68mm

Weight: 35gm

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 300 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	4 base curve, wrap around with integral side shield
Frame	Nylon 6.6	Lens removable from frame
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Polycarbonate	Integral to lens
Sleeve (on temple)	Nylon 6.6	Adjustable to 4 positions
Temple	Nylon 6.6	Adjustable
Hinge	Polycarbonate	3 barrel type, integral to frame sleeve
Screw	Nickel plated	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB410S	 Clear	P Z87 + U6	P Z87 +
SB410ST	 Clear Anti-Fog	P Z87 + U6	P Z87 +
SB410SR	 Clear	P Z87 + U6	P Z87 +
SB420S	 Gray	P Z87 + U6 L3	P Z87 +
SB430S	 Amber	P Z87 + U6	P Z87 +
SB480S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +
SB450SF	 5.0 IR Filter	P Z87 + W5 L5	P Z87 +
SB460SF	 3.0 IR Filter	P Z87 + W3 L3	P Z87 +
SM410S	 Clear	P Z87 + U6	P Z87 +
SN410S	 Clear	P Z87 + U6	P Z87 +
SR410S	 Clear	P Z87 + U6	P Z87 +
SNWR410S	 Clear	P Z87 + U6	P Z87 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

כמויות כרגע במלאי - 8400 יחידות

שחור - 3000

אדום - 1200

כחול - 1200

אדום, לבן וכחול - 3000

* לחברה יש יכולת ליצר 100,000 יחידות המחיר הינו 9.56 ש"ח ליחידה
וזמן האספקה הוא בין 4-5 חודשים.